

Antistatic fabric SF40

- Static dissipative fabric
- For use in manufacturing ESD garments
- IEC 61340-5-1 compatible
- Carbon loaded yarns (conductive yarns) in 4 mm grid
Double carbon loaded yarns on the weft
- Width - 162 cm
- All colors available providing Pantone number
- Composition:
 - 62% Polyester
 - 34% cotton
 - 4% conductive fibers
- Weight - 156 g/sm
- Comfortable and breathable
- Roll = 60-140 meters



Machine washable up to 40⁰ c
Do not bleach
Do not use acid or alkali
Ironing at Medium temperature
Tumble dry at low temperature

Durability

IEC 61340-5-1 Electrical properties maintained after **more than 100** industrial launderings

Technical Information



22 Efal St. POB 3041 Kiryat-Arie, Petah-Tikva 49511, Israel • Tel: 972-3-9231311 • Fax: 972-3-9231511

Electrical properties:

	Test standard	Typical values	Requirements
Point to point resistance Rp	IEC 61340-5-1	$10^5 - 10^7 \Omega$	$R_p \leq 10^{11} \Omega$
Decay time	IEC 61340-2-1	0.5-0.9 seconds Peak voltage $U \leq 150V$	< 2 seconds To 10% of initial value (max peak voltage 1000V)



SF40 ESD Fabric	
White	004001
Light Blue	004002
Grey	004003
Yellow	004004
Red	004005
Green	004006

We believe all the information in these pages including technical data to be reliable. However, we make no warranties expressed or implied and assume no liability regarding any use of this information

K&K preserves its right to alter the composition and materials used in manufacturing the product